

SPECIFICATIONS – MAX FIXAIR-3.0 SC	
AIR VOLUME	800 – 1750 CFM (SEE CURVE)
MOTOR	3.0 HP TEFC, 3450 RPM
VOLTAGE	208/230/460/575/3/60
BLOWER	DIRECT DRIVE, NON-OVERLOADING, BACKWARD-INCLINED ALUMINUM WHEEL
DIMENSIONS (L x W x H)	35 ¼" x 30" x 57"
WEIGHT	350 lbs.
CABINET CONSTRUCTION	14 GA. WELDED STEEL
FINISH	INDUSTRIAL GRADE BAKED ON POWDER COAT PAINT
FILTRATION & EFFICIENCY	2x 21" 80/20 FIRE RETARDANT 185 SQ. FT. PER CARTRIDGE (370 SQ. FT. TOTAL), 99% @ 1 micron
FILTER CLEANING	REVERSE PULSE
COMPRESSED AIR REQUIREMENT:	CLEAN, DRY AIR, 80-90 PSI
FILTER ACCESS	HINGED DOOR
AFTERFILTER	POLYSORB FILTER
DUST DRAWER CAPACITY	1x .5 CUBIC FOOT
CONTROLS	START/STOP MANUAL STARTER
NOISE LEVEL	78 dBA AT 5'

AVAILABLE OPTIONS:

AUTOMATIC SELF CLEANING REVERSE PULSE
 FLOOR STAND AND HOPPER FOR 5 GALLON DRUM
 SUSPENSION MOUNTING BRACKETS
 5 GALLON DRUM LID KIT
 MINIHELIC DIFFERENTIAL PRESSURE GAGE
 CASTORS
 HEPA AFTERFILTERS
 CARBON GRANULE AFTERFILTERS
 WASHABLE POLYESTER SPUN BOND CARTRIDGE

* TEXAS ELECTRONICS CDA. INC. RESERVES THE RIGHT TO MAKE CHANGES IN DESIGN AND SPECIFICATIONS WITHOUT PRIOR NOTICE, TO BETTER IMPROVE OUR PRODUCTS.

MAX AIR SYSTEMS

BY TEXAS ELECTRONICS (CANADA) INC.

2125 MADISON AVE., MONTREAL, QUEBEC H4B 2T2

TEL.:(514) 842-4431, (800) 387-9696 FAX: (514) 842-8641

WWW.MAXAIRSYSTEMS.COM • E-MAIL: INFO@TEXASELEC.COM

(FIXAIR 3.0 SC SPEC.DOC)