

SPECIFICATIONS – MAX MOBILAIR-1.5 SC

AIR VOLUME	600 – 1200 CFM (SEE CURVE)
MOTOR	1.5 HP TEFC, 3450 RPM
VOLTAGE	115/230/1/60 (3 PHASE AVAILABLE)
ELECTRICAL	115 V WITH 10' ELECTRICAL CORD
BLOWER	DIRECT DRIVE, NON-OVERLOADING, BACKWARD-INCLINED ALUMINUM WHEEL
CAPTURE ARM	10' x 6" DIA.
DIMENSIONS (L x W x H)	35 ¼" x 30" x 57"
WEIGHT	350 lbs.
CABINET CONSTRUCTION	14 GA. WELDED STEEL
FINISH	INDUSTRIAL GRADE BAKED ON POWDER COAT PAINT
CASTORS	HEAVY-DUTY 4" DIA. INDUSTRIAL GRADE, SWIVEL AND LOCKING
FILTRATION & EFFICIENCY	2x 21" 80/20 FIRE RETARDANT 185 SQ. FT. PER CARTRIDGE (370 SQ. FT. TOTAL), 99% @ 1 micron
FILTER CLEANING	REVERSE PULSE
COMPRESSED AIR REQUIREMENT:	CLEAN, DRY AIR, 80-90 PSI
FILTER ACCESS	HINGED DOOR
AFTERFILTER	POLYSORB FILTER
CONTROLS	START/STOP MANUAL STARTER
NOISE LEVEL	78 dBA AT 5'

AVAILABLE OPTIONS:

AUTOMATIC SELF CLEANING REVERSE PULSE

HALOGEN LIGHT KIT

MINIHELIC DIFFERENTIAL PRESSURE GAGE

HEPA AFTERFILTER

CARBON GRANULE AFTERFILTER

WASHABLE POLYESTER SPUN BOND CARTRIDGE

* TEXAS ELECTRONICS CDA. INC. RESERVES THE RIGHT TO MAKE CHANGES IN DESIGN AND SPECIFICATIONS WITHOUT PRIOR NOTICE, TO BETTER IMPROVE OUR PRODUCTS.

MAX AIR SYSTEMS

BY TEXAS ELECTRONICS (CANADA) INC.

2125 MADISON AVE., MONTREAL, QUEBEC H4B 2T2

TEL.:(514) 842-4431, (800) 387-9696 FAX: (514) 842-8641

WWW.MAXAIRSYSTEMS.COM • E-MAIL: INFO@TEXASELEC.COM

(MOBILAIR1.5SCSPEC.DOC)