

SPECIFICATIONS – POWERAIR 5.0

AIR VOLUME	SEE POWERAIR 5.0 CURVE
MOTOR	5.0 HP TEFC, C-FACE, 3450 RPM
VOLTAGE	208/230/460/575/3/60
BLOWER WHEEL	DIRECT DRIVE, NON-OVERLOADING, BACKWARD-INCLINED ALUMINUM WHEEL
BLOWER HOUSING CONSTRUCTION	14 GA. WELDED STEEL
WALL MOUNTING BRACKET	14 GA. WELDED STEEL AND ANGLE FRAME
FINISH	INDUSTRIAL GRADE BAKED ON POWDER COAT PAINT
NOISE LEVEL	79 dBA AT 5'
WEIGHT	141 lbs.

AVAILABLE OPTIONS:

MOTOR STARTER
OUTLET TRANSITION
SILENCER

* TEXAS ELECTRONICS RESERVES THE RIGHT TO MAKE CHANGES IN DESIGN AND SPECIFICATIONS WITHOUT PRIOR NOTICE, TO BETTER IMPROVE OUR PRODUCTS.

TEXAS ELECTRONIQUES (CANADA) INC.

2125 MADISON AVE. • MONTREAL, QUEBEC H4B 2T2 • (514) 842-4431 •

FAX: (514) 842-8641 • WWW.MAXAIRSYSTEMS.COM • E-MAIL:

INFO@TEXASELEC.COM

(POWERAIR5.0SPEC.DOC)